RECOMMENDED LUBRICANTS

Climatic conditions	Duckham's	Castrol	Esso	Mobil	Shell	BP	Filtrate	Sternol
*All temperatures above -18° C. (0° F.)	Q 5500	Castrolite	Esso Extra Motor Oil 10W/30	Mobiloil Special 10W/30	Shell Super Motor Oil	Super Visco- Static or Visco-Static	Filtrate 10W/30 Multigrade	Sternol W.W Multigrade 10W/40
Approval for car 20W/40, Filtrate single-viscosity c Engine and tran- circumstances mi * For temperatur WHEEL HUBS, N	20W/50, Mobilo onventional lubri smission lubrican ast any additive t res below —18° C	il Special 20W/ cants supplied ts for the Auto to introduced in C. (0° F.) use m	40, and Castrol by the Compar omatic Transmin nto the lubrican nultigrade S.A.I	XL for temper pies listed in thission versions ats recommend B. 5W/20 oil.	ratures down to is chart. are confined	to -12° C. (10° to those shown	F.), and to m in the main	onograde or
All conditions	Duckham's	Castrolease	Esso	Mobilgrease	Shell	Energrease	Filtrate	Ambroline
	L.B. 10 Grease	L.M.	Multi- purpose Grease H	M.P.	Retinax A	L. 2	Super Lithium Grease	L.H.T.
UPPER CYLIND	ER LUBRICAN	т			1			
All conditions	Duckham's Adcoid Liquid	Castrollo	Esso Upper Cylinder Lubricant	Mobil Upperlube	Shell Upper Cylinder Lubricant	Upper Cylinder Lubricant	Filtrate Petroyle	Sternol Magikoyl
	1 1							
STEERING GEAL	ર							